

If the rule is in BLACK text, then it is the same as 2018.

If the rule is in BLUE text, then it has been changed for 2019.

If any future revisions are made it will be in RED text.

Class Designation: A/M

General Safety: All vehicles must conform with general IHRA safety rules.

Beam Tripper: A front beam tripper is permitted but can only extend 45" forward of the centerline of the front wheel.

Towing Rule: Car must be driven to the scale after each pass. Towing is permitted from the scale to the pit area on every pass. A broken car can be towed to the scales after a pass with tech supervision only.

Engine Coolant: Only water is permitted in the coolant system. Antifreeze or other additives are prohibited.

Hybrids: Import engines in Domestic bodies or Domestic engines in Import bodies are prohibited. All cars must be either Import bodied/powerd or Domestic bodied/powerd.

Body: Any year vehicle is allowed. Lightweight components are limited to hood, front fenders, decklid, hatches, sunroofs, wings, ground effects, bumpers, doors, and roof only. Aftermarket doors must be factory appearing. Quarter panels must remain steel. One-piece front ends are not permitted. No body parts may be removed during competition.

Chassis: All cars must retain complete stock chassis, floorboard, firewall, and frame rails. Frame rails may be modified in front of the strut tower. Notching of chassis for clearance is permitted. Aftermarket "K" members are permitted. All cars can remove spare tire wheel well and cover with sheet metal.

Suspension: All cars must utilize stock front and rear suspension mounts (suspension must be a direct bolt-in to factory location). Aftermarket front control arms, rear control arms, and sub-frame connectors are permitted. Aftermarket struts and shocks are permitted. Wheelie bars are prohibited on all cars.

Lights: Headlights and brake lights are required (one headlight may be removed for induction).

Front Windshield: The front windshield must be either OEM glass or factory appearing polycarbonate windows (For example: Optic Armor, Pro Glass, & Shields type windshield). If factory appearing polycarbonate windshield is used, then it must appear exactly like a factory installed OEM windshield and be at least a 1/4" thick. Tech should not be able to tell the difference. Visible braces are not allowed on front windshield. Screws or rivets on front windshield are permitted but cannot be visible and must be hidden under the factory trim molding.

Side & Rear Windows: OEM glass or lexan side and rear windows are permitted. Braces, screws and rivets are permitted on side and rear windows. If you are running aftermarket doors, we strongly encourage you to use lexan windows with an aftermarket window latch.

Interior: Not required.

Exhaust: Not required. Exhaust may exit anywhere.

Driveline: Aftermarket axles, ring and pinions, final drive, spools, and differentials are permitted. Other OEM or aftermarket center sections and rear-ends may be replaced only if is a direct bolt in. IRS suspension cars may convert to straight axle only if it is a direct bolt in.

Transmission: Manual or Auto transmissions are permitted. Any style automatic transmission is permitted. Trans-brakes are permitted. Manual transmissions are permitted to use aftermarket stock-style clutch-assisted transmissions. Sequential transmissions are prohibited. Aftermarket bell housings are permitted.

Clutch: Three discs maximum (any type of disk material is permitted). Clutch must be manually operated by driver's foot.

Shifter: Shifter must be H-pattern. Strain gauges are permitted. Air shifters are prohibited.

Fuel: All fuels cannot exceed .810 specific gravity. All cars must provide a way for techs to get a fuel sample from the fuel rails.

Fuel System: Electric fuel pumps only are permitted. Aftermarket fuel cells are permitted and may be mounted anywhere in vehicle. All cars must be equipped with a drain valve located on the return side of the fuel rail or regulator to facilitate the removal of fuel samples for fuel check purposes.

Oiling System: Dry sump oil system is only permitted if car was OEM equipped with a dry sump and car is using complete OEM oiling system.

Tires: Maximum size slick or bias ply tire is 28.0" x 11.5". Any size DOT radial tire is permitted, except 315/60/15, 325/50/15, 295/55/15 or 295/60/15.

8-Cylinder Engines – Chevy LT, LS, LQ, and LY series

Engine: LM4, LM7, L31, L33, L59, LT1, LS1, LS2, LS3, LS6, LS7, LQ4, LQ9, LY6 series small blocks permitted. No aftermarket blocks are permitted. Factory rods and cranks only are permitted (factory cranks may be modified). Aftermarket camshaft, hydraulic lifters, valve train, pistons and hardware are permitted (See chart below for max CID).

Bolt-Ons: External bolt-on parts are permitted.

Camshaft: All cars are permitted to run any hydraulic camshaft.

Induction: Engine must be EFI. All OEM intakes are permitted. Any size single throttle body is permitted. The only aftermarket intakes permitted are: MSD Atomic AirForce intakes, Holley Hi-Ram, BBK intakes, Typhoon intakes, and Fast 78mm, 90mm, 92mm, and 102mm intakes (Intake porting is permitted).

Cylinder Heads: OEM cylinder heads only are permitted with the following casting numbers: 035, 241, 243, 317, 364, 373, 452, 706, 716, 799, 806, 821, 823, 853, 862, 873, 895, 933, 5364, 8452. Cylinder head must retain factory valve angle. Any size valve, valve material, or valve job is permitted. Aftermarket cylinder heads are prohibited.

Power Adders: Turbochargers, Superchargers, and Nitrous Oxide are prohibited. All nitrous bottles and solenoids must be removed from car and nitrous nozzles must be capped.

| Driveline | Block | Cylinder Heads | Max Displacement | Car & Driver Minimum Weight |
|----------------------|-------------------------|--|------------------|-----------------------------|
| Straight Axle or IRS | LM4, LM7, L31, L33, L59 | Rectangle or Cathedral Port Cylinder Heads | 327ci. Max | 2700 lbs. |
| Straight Axle or IRS | LS1, LS6 | Rectangle or Cathedral Port Cylinder Heads | 348ci. Max | 2800 lbs. |
| Straight Axle or IRS | LS2, LQ4, LQ9, LY6 | Rectangle or Cathedral Port Cylinder Heads | 366ci. Max | 2900 lbs. |
| Straight Axle or IRS | LS3 | Rectangle or Cathedral Port Cylinder Heads | 380ci. Max | 3050 lbs. |
| IRS Only | LT1 | Rectangle Port Cylinder Heads | 374ci. Max | 3000 lbs. |
| IRS Only | LS7 | Rectangle Port Cylinder Heads | 427ci. Max | 3150 lbs. |

* Manual transmission: Deduct 200 lbs.

* Cars with IRS: Deduct 50 lbs.

* Cars with ported heads or LS7 heads: Add 150 lbs.

* Cars equipped with Rectangle Port Heads: Add 50 lbs.

* LT1 & LS7 cars equipped with aftermarket cam: Add 150 lbs.

* LT1 & LS7 cars equipped with MSD Atomic AirForce or Holley Hi-Ram intake: Add 75 lbs.

If the rule is in BLACK text, then it is the same as 2018. If the rule is in BLUE text, then it has been changed for 2019. If any future revisions are made it will be in RED text.

8-Cylinder Engines - Ford 302W

Engine: Any 302 style 8.2 deck block is permitted. Roller Rockers are permitted. Factory stroke is required. Max CID is 313ci.
Bolt-Ons: External bolt-on parts are permitted.
Camshaft: Maximum camshaft lift .650 intake and .650 exhaust any duration as checked at valve.
Induction: Engine may be EFI or carbureted. All aftermarket EFI intakes are permitted. Spyder and Sheet metal Intakes are prohibited. Carburetor Induction is limited to a single plane or dual plane intake. Maximum carb size 750cfm.
Cylinder Heads: All cylinder heads must retain stock valve angle. Any valve job is permitted.
Power Adders: Turbochargers, Superchargers, and Nitrous Oxide are prohibited. All nitrous bottles and solenoids must be removed from car and nitrous nozzles must be capped.

| Cylinder Heads | Max Displacement | Car & Driver Minimum Weight |
|--|------------------|-----------------------------|
| OEM E7 heads | 313ci. Max | 2600 lbs. |
| Cast Iron GT-40, and Aluminum GT-40X | 313ci. Max | 2650 lbs. |
| AFR 165cc Heads: 1402, 1472, and 1399 AFR 185cc Heads: 1388, 1422, 1387, 1492, and 1420 Holley Aluminum Heads Brodix: 1051004, 171cc Cylinder Head Edelbrock: 60329, 60229, 60379, and 60289 only Dart: Pro 1 Aluminum 175cc Head RHS Pro Action: 35014-01, 35014-02, 35010-02, and 35010-01 World Products (Cast Iron Windsor JR): 053030-1 and 053030-2 Promaxx: 175cc and 185cc | 313ci. Max | 2850 lbs. |
| Trickflow Twisted Wedge: 15-degree valve angle only (Maximum intake runner 205cc) | 313ci. Max | 2900 lbs. |
| Trickflow Twisted Wedge: 11-degree valve angle only (Maximum intake runner 205cc) | 313ci. Max | 3000 lbs. |

* Automatic overdrive transmissions: Deduct 100 lbs.
 * Un-Ported cylinder heads: Deduct 100 lbs.
 * Manual Transmission Cars: Add 75 lbs.

8-Cylinder Engines - Ford 5.0 Modular

Engine: OEM 5.0 modular blocks only are permitted. Max CID is 321ci.
Bolt-Ons: External bolt-on parts are permitted.
Camshaft: Maximum camshaft lift .550 intake and .550 exhaust any duration as checked at valve.
Induction: Engine must be EFI. All OEM intakes are permitted. The only aftermarket intakes permitted is a Boss Intake.
Cylinder Heads: Any valve job is permitted. Un-Ported or Ported OEM cylinder heads only.
Power Adders: Turbochargers, Superchargers, and Nitrous Oxide are prohibited. All nitrous bottles and solenoids must be removed from car and nitrous nozzles must be capped.

| Cylinder Heads | Max Displacement | Car & Driver Minimum Weight |
|-------------------|--------------------|-----------------------------|
| Un-Ported as cast | Up to 313ci. | 3150 lbs. |
| Porting Permitted | Up to 313ci. | 3225 lbs. |
| Un-Ported as cast | 314ci – 321ci. Max | 3250 lbs. |
| Porting Permitted | 314ci – 321ci. Max | 3325 lbs. |

8-Cylinder Engines - Ford 4.6 Modular (4-Valve)

Engine: OEM 4.6 modular blocks are permitted. Max CID is 302ci.
Bolt-Ons: External bolt-on parts are permitted.
Camshaft: Maximum camshaft lift .550 intake and .550 exhaust any duration as checked at valve.
Induction: Engine must be EFI. Only OEM intakes are permitted.
Cylinder Heads: Any valve job is permitted. Un-Ported or Ported OEM cylinder heads only.
Power Adders: Turbochargers, Superchargers, and Nitrous Oxide are prohibited. All nitrous bottles and solenoids must be removed from car and nitrous nozzles must be capped.

| Valves | Cylinder Heads | Max Displacement | Car & Driver Minimum Weight |
|---------|-------------------------------|------------------|-----------------------------|
| 4-valve | OEM Heads (Un-Ported as cast) | 302ci. Max | 3025 lbs. |
| 4-valve | OEM Heads (Porting Permitted) | 302ci. Max | 3125 lbs. |

* Automatic overdrive transmissions: Deduct 100 lbs.

8-Cylinder Engines - Ford 4.6 Modular (3-Valve)

Engine: OEM 4.6 modular blocks are permitted. Max CID is 302ci.
Bolt-Ons: External bolt-on parts are permitted.
Camshaft: Maximum camshaft lift .550 intake and .550 exhaust any duration as checked at valve.
Induction: Engine must be EFI. All OEM intakes are permitted. The only aftermarket intakes permitted are: C&L, JPC, and FRPP. Fabricated sheet metal intakes are prohibited.
Cylinder Heads: Any valve job is permitted. Un-Ported or Ported OEM cylinder heads only.
Power Adders: Turbochargers, Superchargers, and Nitrous Oxide are prohibited. All nitrous bottles and solenoids must be removed from car and nitrous nozzles must be capped.

| Valves | Cylinder Heads | Max Displacement | Car & Driver Minimum Weight |
|---------|-------------------------------|------------------|-----------------------------|
| 3-valve | OEM Heads (Un-Ported as cast) | 302ci. Max | 2925 lbs. |
| 3-valve | OEM Heads (Porting Permitted) | 302ci. Max | 3025 lbs. |

* Automatic overdrive transmissions: Deduct 100 lbs.

If the rule is in BLACK text, then it is the same as 2018. If the rule is in BLUE text, then it has been changed for 2019. If any future revisions are made it will be in RED text.

8-Cylinder Engines - Ford 4.6 Modular (2-Valve)

Engine: OEM 4.6 modular blocks are permitted. Max CID is 302ci.
Bolt-Ons: External bolt-on parts are permitted.
Camshaft: Maximum camshaft lift .550 intake and .550 exhaust any duration as checked at valve.
Induction: Engine must be EFI. All OEM intakes are permitted. The only aftermarket intakes permitted are: Bullitt, Trickflow, P51, and Professional Products intakes. Fabricated sheet metal intakes are prohibited.
Cylinder Heads: Any valve job is permitted. Un-Ported or Ported OEM cylinder heads are permitted. Ford Racing SVO 2v or Trickflow 2v Un-Ported aftermarket cylinder heads are permitted.
Power Adders: Turbochargers, Superchargers, and Nitrous Oxide are prohibited. All nitrous bottles and solenoids must be removed from car and nitrous nozzles must be capped.

| Valves | Cylinder Heads | Max Displacement | Car & Driver Minimum Weight |
|---------|---|------------------|-----------------------------|
| 2-valve | Any Heads Permitted (Porting Permitted) | 302ci. Max | 2800 lbs. |

* Automatic overdrive transmissions: Deduct 100 lbs.