

If the rule is in BLACK text, then it is the same as 2018.

If the rule is in BLUE text, then it has been changed for 2019.

If any future revisions are made it will be in RED text.

**Class Designation:** WvT

**General Safety:** All vehicles must conform with general IHRA safety rules.

**Beam Tripper:** A front beam tripper is permitted but can only extend 45° forward of the centerline of the front wheel.

**Engine Coolant:** Only water is permitted in the coolant system. Antifreeze or other additives are prohibited.

**Hybrids:** Import engines in Domestic bodies or Domestic engines in Import bodies are prohibited. All cars must be either Import bodied/powered or Domestic bodied/powered.

**Body:** Must have an import body or a domestic sport compact body. Any year vehicle is allowed. Lightweight components are limited to hood, front fenders, decklid, hatches, sunroofs, wings, ground effects, bumpers, doors, and roof only. Quarter panels must remain steel. One-piece front ends are permitted. No body parts may be removed during competition.

**Chassis:** All cars may run 3/4 chassis but must retain OEM firewall and OEM strut towers in OEM location and be within 2" of OEM wheelbase. **VW cars must use OEM frame only.** Aftermarket "K" members are permitted.

**Suspension:** All cars must utilize stock mounting points for front suspension in the stock location. Any type rear suspension is permitted. Aftermarket front and rear control arms, struts, and shocks are permitted. Sub-frame connectors are permitted. Wheelie bars are permitted on all cars.

**Windows:** OEM glass or lexan windows are permitted. **If you are using aftermarket doors or lexan windows, then a steel frame around the lexan window or a window latch is required.**

**Transmission:** Any type transmission is permitted. Trans-brakes are permitted. Aftermarket bell housings are permitted.

**Clutch:** Any style clutch is permitted.

**Shifter:** Any style shifter is permitted. Strain gauges are permitted.

**Fuel:** Any fuel is permitted.

**Engine:** OEM or Aftermarket blocks are permitted.

**Turbochargers:** Turbochargers are measured at the inducer wheel where the leading edge of the inducer wheel meets the housing.

**Nitrous Oxide:** Any style nitrous oxide system is permitted for combinations that allow nitrous oxide. If nitrous oxide is not permitted for your combination, then bottles and solenoids must be removed from car and nitrous nozzles must be capped.

**Tires:** Slicks are limited to a 32.0"x14.5" or 33"x10.5W"

**Engine Containment Device:** Engine diaper or catch pan device to capture oil and/or debris in the event of engine and/or transmission failure mandatory. Where exhaust header passes directly under oil pan, a two-piece diaper may be utilized. If a catch pan device is used, catch pan must employ minimum 2-inch-high lips on all sides. Lips must be covered or curved inward, so as to contain oil in pan. Catch pan must cover entire area below the engine/transmission. Catch pan must extend from radiator support to firewall and from frame rail to frame rail. In all cases, lips must be adequate enough to contain oil in the catch pan. Should a competitor spill excessive oil from the catch pan and debris onto the track, he or she may be disqualified from further competition at the sole and absolute discretion of the event director.

Engine	Driveline	Maximum Turbocharger	Nitrous Oxide	Car & Driver Minimum Weight
2-rotor	RWD	Any 91.9 mm single	Nitrous ok	2000 lbs.
2-rotor	RWD	No Restrictions	Nitrous ok	2100 lbs.
* Cars with 92" wheelbase or shorter: Deduct 150 lbs.				

Engine	Driveline	Maximum Turbocharger	Nitrous Oxide	Car & Driver Minimum Weight
4-cylinder	RWD	Any 76.9 mm single	Nitrous Prohibited	2000 lbs.
4-cylinder	RWD	Any 82.9 mm single	Nitrous Prohibited	2100 lbs.
4-cylinder	RWD	Any 88.9 mm single	Nitrous Prohibited	2200 lbs.
* Cars with 92" wheelbase or shorter: Deduct 150 lbs.				

Engine	Driveline	Maximum Turbocharger	Nitrous Oxide	Car & Driver Minimum Weight
6-cylinder	RWD	GT4788 / PT8884 / T48074 / S500-88	Nitrous permitted on auto cars only	2350 lbs.
6-cylinder	RWD	Any 88.9 mm single	Nitrous permitted on auto cars only	2500 lbs.
6-cylinder	RWD	Any 91.9 mm single	Nitrous permitted on auto cars only	2600 lbs.
6-cylinder	AWD	No Restrictions	Nitrous ok	3000 lbs.
* Automatic Cars: Deduct 200 lbs.				
* Cars with 92" wheelbase or shorter: Deduct 150 lbs.				