

If the rule is in BLACK text, then it is the same as 2017.

If the rule is in BLUE text, then it has been changed for 2018.

If any future revisions are made it will be in RED text.

Class Designation: T/S

General Safety: All vehicles must conform with general IHRA safety rules.

Beam Tripper: A front beam tripper is permitted but can only extend 45° forward of the centerline of the front wheel.

Engine Coolant: Only water is permitted in the coolant system. Antifreeze or other additives are prohibited.

Hybrids: Import engines in Domestic bodies or Domestic engines in Import bodies are prohibited. All cars must be either Import bodied/powered or Domestic bodied/powered.

Body: Any year vehicle is allowed. Lightweight components are limited to hood, front fenders, decklid, hatches, sunroofs, wings, ground effects, bumpers, doors, and roof only. Aftermarket doors must be factory appearing. Quarter panels must remain steel. One-piece front ends are not permitted. No body parts may be removed during competition.

Chassis: All cars must retain complete stock chassis, floorboard, firewall, and frame rails. Frame rails may be modified in front of the strut tower. Notching of chassis for clearance is permitted. Aftermarket "K" members are permitted. All cars can remove spare tire wheel well and cover with sheet metal.

Suspension: All cars must utilize stock front and rear suspension mounts (suspension must be a direct bolt-in to factory location). Aftermarket front control arms, rear control arms, and sub-frame connectors are permitted. Aftermarket struts and shocks are permitted. Wheelie bars are prohibited on all cars.

Lights: Headlights and brake lights are required (one headlight may be removed for induction).

Front Windshield: The front windshield must be either OEM glass or factory appearing polycarbonate windows (For example: Optic Armor, Pro Glass, & Shields type windshield). If factory appearing polycarbonate windshield is used, then it must appear exactly like a factory installed OEM windshield and be at least a 1/4" thick. Tech should not be able to tell the difference. Visible braces are not allowed on front windshield. Screws or rivets on front windshield are permitted but cannot be visible and must be hidden under the factory trim molding.

Side & Rear Windows: OEM glass or lexan side and rear windows are permitted. Braces, screws and rivets are permitted on side and rear windows. If you are running aftermarket doors, we strongly encourage you to use lexan windows with an aftermarket window latch.

Interior: Stock dashboard and full interior from front seats forward is required (passenger seat may be removed). Headliner is not required. Doors must have a factory or aftermarket skin of some type on the inside.

Exhaust: Muffler(s) are required unless vehicle is turbocharged. Exhaust may exit anywhere.

Driveline: Aftermarket axles, ring and pinions, final drive, spools, and differentials are permitted. Other OEM or aftermarket center sections and rear-ends may be replaced only if it is a direct bolt in. IRS suspension cars may convert to straight axle only if it is a direct bolt in.

Transmission: Manual or Auto transmissions are permitted. Any style automatic transmission is permitted. Trans-brakes are permitted. Manual transmissions are permitted to use aftermarket stock-style clutch-assisted transmissions. Sequential transmissions are prohibited. Aftermarket bell housings are permitted.

Clutch: Three discs maximum (any type of disk material is permitted). Clutch must be manually operated by driver's foot.

Shifter: Shifter must be H-pattern. Strain gauges are permitted. Air shifters are prohibited.

Fuel: Gasoline or any ethanol blended fuel is permitted. All fuels cannot exceed .799 specific gravity. Fuels will be checked with a digital specific gravity tester.

Fuel System: Electric fuel pumps only are permitted. Aftermarket fuel cells are permitted and may be mounted anywhere in vehicle. All cars must be equipped with a drain valve located on the return side of the fuel rail or regulator to facilitate the removal of fuel samples for fuel check purposes.

Oiling System: Any type oiling system is permitted.

Tires: Maximum size slick or bias ply tire is 28.0" x 11.5". Any size DOT radial tire is permitted, except 315/60/15, 325/50/15, 295/55/15 or 295/60/15

Engine Containment Device: Engine diaper or catch pan device to capture oil and/or debris in the event of engine failure mandatory. If a catch pan device is used, catch pan must employ minimum 2-inch-high lips on all sides. Lips must be covered or curved inward, so as to contain oil in pan. Catch pan must cover entire area below the engine. Catch pan must extend from radiator support to firewall and from frame rail to frame rail. In all cases, lips must be adequate enough to contain oil in the catch pan. Should a competitor spill excessive oil from the catch pan and debris onto the track, he or she may be disqualified from further competition at the sole and absolute discretion of the event director.

6-Cylinder Engines – Buick

Engine: Any internal engine modifications are permitted. Aftermarket blocks are prohibited.

Induction: Engine must be EFI. Stock style EFI intake manifolds with a forward facing throttle body only are permitted. No fabricated or sheet metal intakes.

Turbochargers: Turbochargers are measured at the inducer wheel where the leading edge of the inducer wheel meets the housing. The contour from the inducer to the exducer must be continuous without steps. The use of restrictor plates, stepped inlet housings or reducers in an effort to limit compressor size opening is not acceptable. Compressor housing cannot be modified from the leading edge of the inducer to the trailing edge of the exducer. All inducer surge ports must be perpendicular to the shaft and limited in location to the leading edge of the inducer. See chart below for turbo size restrictions.

Nitrous Oxide: Not permitted. All nitrous bottles and solenoids must be removed from car and nitrous nozzles must be capped.

Intercooling: Air intercoolers only are permitted. Water injection is permitted. Methanol injection is prohibited.

Maximum Turbocharger	Nitrous Oxide	Car & Driver Minimum Weight
72.9 mm single (Compressor Exducer 106.9mm Max) T4 Max Size	Nitrous Prohibited	3500 lbs.

If the rule is in BLACK text, then it is the same as 2017.

If the rule is in BLUE text, then it has been changed for 2018.

If any future revisions are made it will be in RED text.

8-Cylinder Engines – Chevy LT, LS, LQ, and LY series

Engine: Only the following small blocks are permitted: LT1, LT4, LS1, LS2, LS3, LS6, LS7, LS9, LSA, LQ4, LQ9, and LY6, series blocks only. No aftermarket blocks are permitted. Any internal engine modifications are permitted. Max CID is 427ci.

Induction: Engine must be EFI or carbureted. Aftermarket commercially available intakes only are permitted. Carb style intakes are only permitted on naturally aspirated or nitrous cars. No fabricated or sheet metal intakes.

Cylinder Heads: Aftermarket cylinder heads are permitted. Cylinder heads may be ported. *Aftermarket* canted valve heads and billet heads are prohibited.

Turbochargers: Turbochargers are measured at the inducer wheel diameter at the point where the leading edge of the compressor wheel meets the inlet housing. Cannot combine with nitrous oxide. Liquid intercoolers and air intercoolers are permitted. See table below for max turbocharger size.

Superchargers: Superchargers are permitted and must run off a serpentine belt. Cannot combine with nitrous oxide (nitrous may be combined with LSA superchargers only). Liquid intercoolers and air intercoolers are permitted. See table below for approved superchargers.

Nitrous Oxide: See table below for restrictions. Nitrous purge must exit engine bay. Nitrous "Push" systems are prohibited. *Nitrous cannot be combined with a Turbocharger.*

Power Adder	Max Displacement	Car & Driver Minimum Weight
NITROUS OXIDE: Limited to a single stage fogger system (with a .034 nitrous jet)	Up to 385ci.	3150 lbs.
NITROUS OXIDE: Limited to a single plate (with a single .110 nitrous jet)	Up to 385ci.	3150 lbs.
NITROUS OXIDE: Limited to a single plate (with a single .092 nitrous jet)	386ci - 427ci. Max	3350 lbs.
(Compressor Wheel 76.9mm Inducer / 116.9mm Exducer) (Turbine Wheel 96.9 Inducer / 88.9 Exducer) T4 only	427ci. Max	3775 lbs.
(Compressor Wheel 86.9mm Inducer / 112.9mm Exducer) (Turbine Wheel 89.9 Inducer / 85.9 Exducer) T4 only	427ci. Max	3950 lbs.
(Compressor Wheel 76.9mm Inducer / 116.9mm Exducer) (Turbine Wheel 96.9 Inducer / 88.9 Exducer) T6 only	427ci. Max	3975 lbs.
(Compressor Wheel 80.9mm Inducer / 133.9mm Exducer) (Turbine Wheel 111.9 Inducer / 102.9 Exducer) T6 only	427ci. Max	4200 lbs.
KENNE BELL: 2.1, 2.6 WHIPPLECHARGER: 2.3 PAXTON: Novi 1000, 1200 ANY MAGNUSON, EATON, OR TVS VORTECH: V-1 A, B, S, Si, V-2 S-Trim, V-2 Si-Trim, V-3 Si-Trim ATI PROCHARGER: P1SC, P1SC-2, P1SC-H GM: LSA, ZR1	427ci. Max	3500 lbs.
KENNE BELL: 2.8 WHIPPLECHARGER: 2.9 PAXTON: Novi 2000, 2200 VORTECH: T, JT ATI PROCHARGER: D1SC, D1, D1R	427ci. Max	3600 lbs.
KENNE BELL: 3.6 WHIPPLECHARGER: 3.4 ATI PROCHARGER: F-1, F-1D, F-1A	427ci. Max	3750 lbs.
ATI PROCHARGER: D1-X	427ci. Max	3800 lbs.
VORTECH: YS, YSI Trim, YSI-2200, V24-YSI Trim ATI PROCHARGER: F-1C-91, F-1A-91, F-1A-94	427ci. Max	3900 lbs.
WHIPPLECHARGER: 4.0 ATI PROCHARGER: F1-R	427ci. Max	4050 lbs.
VORTECH: V-30 94B ATI PROCHARGER: F1-X	427ci. Max	4200 lbs.

* Supercharged cars with 395ci or smaller engines: Deduct 50 lbs.

* Manual transmission: Deduct 100 lbs.

* OEM cylinder heads: Deduct 75 lbs.

* IRS cars: Deduct 50 lbs.

* Centrifugal Supercharged & Turbocharged cars with liquid intercooler: Add 100 lbs.

* Supercharged cars with nitrous oxide (with a single .062 jet max): Add 300 lbs.

8-Cylinder Engines - Ford 302W

Engine: Any 302 style 8.2 deck block is permitted. Any internal engine modifications are permitted. Max CID is 347ci.

Induction: Naturally aspirated cars may be EFI or carbureted. Maximum carb size 750cfm. Commercially available aftermarket intakes only. No fabricated or sheet metal intakes.

Cylinder Heads: In-line cylinder heads only are permitted with stock valve angles. Cylinder heads may be ported.

Turbochargers: Not permitted.

Superchargers: Superchargers are permitted and must run off a serpentine belt. Cannot combine with nitrous oxide. Air intercoolers only are permitted. See table below for approved superchargers.

Nitrous Oxide: See table below for restrictions. Nitrous purge must exit engine bay. Nitrous "Push" systems are prohibited. *Nitrous cannot be combined with Supercharger.*

Power Adder	Max Displacement	Car & Driver Minimum Weight
NITROUS OXIDE: Limited to a single plate (with a single .100 nitrous jet)	347ci. Max	2850 lbs.
NITROUS OXIDE: Limited to a 2-stage plate (with two .070 nitrous jets)	347ci. Max	3000 lbs.
PAXTON: Novi 1000, 1200 VORTECH: V-1 A, B, S, Si, V-2 S-Trim, V-2 Si-Trim, V-3 Si-Trim ATI PROCHARGER: P1SC, P1SC-2, P1SC-H	347ci. Max	3150 lbs.
PAXTON: Novi 2000, 2200 VORTECH: T, JT ATI PROCHARGER: D1SC, D1, D1R	347ci. Max	3300 lbs.

* Manual transmission: Deduct 100 lbs.

* 311ci or smaller engines: Deduct 150 lbs.

If the rule is in **BLACK** text, then it is the same as 2017.

If the rule is in **BLUE** text, then it has been changed for 2018.

If any future revisions are made it will be in **RED** text.

8-Cylinder Engines - Ford 5.0 Modular

Engine: Only OEM 5.0 modular blocks are permitted. Any internal engine modifications are permitted. Max CID is 311ci.

Induction: Engine must be EFI. Aftermarket commercially available intakes only are permitted. No fabricated or sheet metal intakes.

Cylinder Heads: Un-Ported or Ported OEM cylinder heads only.

Turbochargers: Turbochargers are measured at the inducer wheel diameter at the point where the leading edge of the compressor wheel meets the inlet housing. Cannot combine with nitrous oxide. Liquid intercoolers and air intercoolers are permitted. See table below for max turbocharger size.

Superchargers: Superchargers are permitted and must run off a serpentine belt. Cannot combine with nitrous oxide. Liquid intercoolers and air intercoolers are permitted. See table below for approved superchargers.

Nitrous Oxide: Not permitted. All nitrous bottles and solenoids must be removed from car and nitrous nozzles must be capped.

Power Adder	Max Displacement	Car & Driver Minimum Weight
(Compressor Wheel 76.9mm Inducer / 116.9mm Exducer) (Turbine Wheel 96.9 Inducer / 88.9 Exducer) T4 only	311ci. Max	3800 lbs.
(Compressor Wheel 86.9mm Inducer / 112.9mm Exducer) (Turbine Wheel 89.9 Inducer / 85.9 Exducer) T4 only	311ci. Max	3975 lbs.
(Compressor Wheel 76.9mm Inducer / 116.9mm Exducer) (Turbine Wheel 96.9 Inducer / 88.9 Exducer) T6 only	311ci. Max	4000 lbs.
KENNE BELL: 2.1, 2.6 WHIPPLECHARGER: 2.3 PAXTON: Novi 1000, 1200 ANY MAGNUSON, EATON, OR TVS VORTECH: V-1 A, B, S, Si, V-2 S-Trim, V-2 Si-Trim, V-3 Si-Trim ATI PROCHARGER: P1SC, P1SC-2, P1SC-H	311ci. Max	3350 lbs.
KENNE BELL: 2.8 WHIPPLECHARGER: 2.9 PAXTON: Novi 2000, 2200 VORTECH: T, JT ATI PROCHARGER: D1SC, D1, D1R	311ci. Max	3550 lbs.
KENNE BELL: 3.6 WHIPPLECHARGER: 3.4 ATI PROCHARGER: F-1, F-1D, F-1A	311ci. Max	3650 lbs.
WHIPPLECHARGER: 4.0 VORTECH: YS, YSI Trim, V24-YSI Trim ATI PROCHARGER: F-1C-91, F-1A-91	311ci. Max	3750 lbs.

* Manual transmission: Deduct 100 lbs.
 * Turbocharged cars with cast inducer wheel: deduct 100 lbs.
 * Centrifugal Supercharged & Turbocharged cars with liquid intercooler: Add 100 lbs.

8-Cylinder Engines - Ford 5.4 Modular and Ford 5.8 Modular

Engine: Only OEM 5.4 and 5.8 modular blocks are permitted. Any internal engine modifications are permitted. Max CID is 365ci.

Induction: Engine must be EFI. Aftermarket commercially available intakes only are permitted. No fabricated or sheet metal intakes.

Cylinder Heads: Un-Ported or Ported OEM cylinder heads only.

Turbochargers: Not permitted.

Superchargers: Superchargers are permitted and must run off a serpentine belt. Cannot combine with nitrous oxide. Liquid intercoolers and air intercoolers are permitted. See table below for approved superchargers.

Nitrous Oxide: Not permitted. All nitrous bottles and solenoids must be removed from car and nitrous nozzles must be capped.

Power Adder	Max Displacement	Car & Driver Minimum Weight
KENNE BELL: 2.1, 2.6 WHIPPLECHARGER: 2.3 PAXTON: Novi 1000, 1200 ANY MAGNUSON, EATON, OR TVS VORTECH: V-1 A, B, S, Si, V-2 S-Trim, V-2 Si-Trim, V-3 Si-Trim ATI PROCHARGER: P1SC, P1SC-2, P1SC-H	365ci. Max	3400 lbs.
KENNE BELL: 2.8 WHIPPLECHARGER: 2.9 PAXTON: Novi 2000, 2200 VORTECH: T, JT ATI PROCHARGER: D1SC, D1, D1R	365ci. Max	3600 lbs.
KENNE BELL: 3.6 WHIPPLECHARGER: 3.4 ATI PROCHARGER: F-1, F-1D, F-1A	365ci. Max	3700 lbs.
WHIPPLECHARGER: 4.0 VORTECH: YS, YSI Trim, V24-YSI Trim ATI PROCHARGER: F-1C-91, F-1A-91	365ci. Max	3800 lbs.

* Manual transmission: Deduct 100 lbs.
 * Cars with 340ci or smaller engines: Deduct 50 lbs.
 * Centrifugal Supercharged cars with liquid intercooler: Add 100 lbs.

8-Cylinder Engines - Ford 4.6 Modular (4-Valve)

Engine: Any 4.6 block is permitted. Any internal engine modifications are permitted. Max CID is 302ci.

Induction: Engine must be EFI. Aftermarket commercially available intakes only are permitted. No fabricated or sheet metal intakes.

Cylinder Heads: Un-Ported or Ported OEM cylinder heads only.

Turbochargers: Turbochargers are measured at the inducer wheel diameter at the point where the leading edge of the compressor wheel meets the inlet housing. Cannot combine with nitrous oxide. Liquid intercoolers and air intercoolers are permitted. See table below for max turbocharger size.

Superchargers: Superchargers are permitted and must run off a serpentine belt. Cannot combine with nitrous oxide. Liquid intercoolers and air intercoolers are permitted. See table below for approved superchargers.

Nitrous Oxide: Not permitted. All nitrous bottles and solenoids must be removed from car and nitrous nozzles must be capped.

Power Adder	Max Displacement	Car & Driver Minimum Weight
(Compressor Wheel 76.9mm Inducer / 116.9mm Exducer) (Turbine Wheel 96.9 Inducer / 88.9 Exducer) T4 only	302ci. Max	3650 lbs.
(Compressor Wheel 86.9mm Inducer / 112.9mm Exducer) (Turbine Wheel 89.9 Inducer / 85.9 Exducer) T4 only	302ci. Max	3825 lbs.
(Compressor Wheel 76.9mm Inducer / 116.9mm Exducer) (Turbine Wheel 96.9 Inducer / 88.9 Exducer) T6 only	302ci. Max	3850 lbs.
KENNE BELL: 2.1, 2.6 WHIPPLECHARGER: 2.3 PAXTON: Novi 1000, 1200 ANY MAGNUSON, EATON, OR TVS VORTECH: V-1 A, B, S, Si, V-2 S-Trim, V-2 Si-Trim, V-3 Si-Trim ATI PROCHARGER: P1SC, P1SC-2, P1SC-H	302ci. Max	3150 lbs.
KENNE BELL: 2.8 WHIPPLECHARGER: 2.9 PAXTON: Novi 2000, 2200 VORTECH: T, JT ATI PROCHARGER: D1SC, D1, D1R	302ci. Max	3250 lbs.
KENNE BELL: 3.6 WHIPPLECHARGER: 3.4 ATI PROCHARGER: F-1, F-1D, F-1A	302ci. Max	3350 lbs.
WHIPPLECHARGER: 4.0 VORTECH: YS, YSI Trim, V24-YSI Trim ATI PROCHARGER: F-1C-91, F-1A-91	302ci. Max	3500 lbs.

* Manual transmission: Deduct 100 lbs.
 * Cars with 289ci or smaller engines: Deduct 50 lbs.
 * Turbocharged cars with cast inducer wheel: deduct 100 lbs.
 * Centrifugal Supercharged & Turbocharged cars with liquid intercooler: Add 100 lbs.

If the rule is in BLACK text, then it is the same as 2017.

If the rule is in BLUE text, then it has been changed for 2018.

If any future revisions are made it will be in RED text.

8-Cylinder Engines - Ford 4.6 Modular (3-Valve)

Engine: Any 4.6 block is permitted. Any internal engine modifications are permitted. Max CID is 302ci.

Induction: Engine must be EFI. Aftermarket commercially available intakes only are permitted. No fabricated or sheet metal intakes.

Cylinder Heads: Un-Ported or Ported OEM cylinder heads only.

Turbochargers: Turbochargers are measured at the inducer wheel diameter at the point where the leading edge of the compressor wheel meets the inlet housing. Cannot combine with nitrous oxide. Liquid intercoolers and air intercoolers are permitted. See table below for max turbocharger size.

Superchargers: Superchargers are permitted and must run off a serpentine belt. Cannot combine with nitrous oxide. Liquid intercoolers and air intercoolers are permitted. See table below for approved superchargers.

Nitrous Oxide: Not permitted. All nitrous bottles and solenoids must be removed from car and nitrous nozzles must be capped.

Power Adder	Max Displacement	Car & Driver Minimum Weight
(Compressor Wheel 76.9mm Inducer / 116.9mm Exducer) (Turbine Wheel 96.9 Inducer / 88.9 Exducer) T4 only	302ci. Max	3550 lbs.
(Compressor Wheel 86.9mm Inducer / 112.9mm Exducer) (Turbine Wheel 89.9 Inducer / 85.9 Exducer) T4 only	302ci. Max	3725 lbs.
(Compressor Wheel 76.9mm Inducer / 116.9mm Exducer) (Turbine Wheel 96.9 Inducer / 88.9 Exducer) T6 only	302ci. Max	3750 lbs.
KENNE BELL: 2.1, 2.6 WHIPPLECHARGER: 2.3 PAXTON: Novi 1000, 1200 ANY MAGNUSON, EATON, OR TVS VORTECH: V-1 A, B, S, Si, V-2 S-Trim, V-2 Si-Trim, V-3 Si-Trim ATI PROCHARGER: P1SC, P1SC-2, P1SC-H	302ci. Max	3050 lbs.
KENNE BELL: 2.8 WHIPPLECHARGER: 2.9 PAXTON: Novi 2000, 2200 VORTECH: T, JT ATI PROCHARGER: D1SC, D1, D1R	302ci. Max	3150 lbs.
WHIPPLECHARGER: 3.4 ATI PROCHARGER: F-1, F-1D, F-1A	302ci. Max	3250 lbs.
VORTECH: YS, YSI Trim, V24-YSI Trim ATI PROCHARGER: F-1C-91, F-1A-91	302ci. Max	3400 lbs.

* Manual transmission: Deduct 100 lbs.
 * Turbocharged cars with cast inducer wheel: deduct 100 lbs.
 * Cars with 289ci or smaller engines: Deduct 50 lbs.
 * Centrifugal Supercharged & Turbocharged cars with liquid intercooler: Add 100 lbs.

8-Cylinder Engines - Ford 4.6 Modular (2-Valve)

Engine: Any 4.6 block is permitted. Any internal engine modifications are permitted. Max CID is 302ci.

Induction: Engine must be EFI. Aftermarket commercially available intakes only are permitted. No fabricated or sheet metal intakes.

Cylinder Heads: OEM cylinder heads, Ford Racing SVO 2v cylinder heads, or Trickflow 2v cylinder heads are permitted. Cylinder heads may be Un-Ported or Ported.

Turbochargers: Turbochargers are measured at the inducer wheel diameter at the point where the leading edge of the compressor wheel meets the inlet housing. Cannot combine with nitrous oxide. Liquid intercoolers and air intercoolers are permitted. See table below for max turbocharger size.

Superchargers: Superchargers are permitted and must run off a serpentine belt. Cannot combine with nitrous oxide. Liquid intercoolers and air intercoolers are permitted. See table below for approved superchargers.

Nitrous Oxide: Not permitted. All nitrous bottles and solenoids must be removed from car and nitrous nozzles must be capped.

Power Adder	Max Displacement	Car & Driver Minimum Weight
(Compressor Wheel 76.9mm Inducer / 116.9mm Exducer) (Turbine Wheel 96.9 Inducer / 88.9 Exducer) T4 only	302ci. Max	3450 lbs.
(Compressor Wheel 86.9mm Inducer / 112.9mm Exducer) (Turbine Wheel 89.9 Inducer / 85.9 Exducer) T4 only	302ci. Max	3625 lbs.
(Compressor Wheel 76.9mm Inducer / 116.9mm Exducer) (Turbine Wheel 96.9 Inducer / 88.9 Exducer) T6 only	302ci. Max	3650 lbs.
KENNE BELL: 2.1, 2.6 WHIPPLECHARGER: 2.3 PAXTON: Novi 1000, 1200 ANY MAGNUSON, EATON, OR TVS VORTECH: V-1 A, B, S, Si, V-2 S-Trim, V-2 Si-Trim, V-3 Si-Trim ATI PROCHARGER: P1SC, P1SC-2, P1SC-H	302ci. Max	2950 lbs.
KENNE BELL: 2.8 WHIPPLECHARGER: 2.9 PAXTON: Novi 2000, 2200 VORTECH: T, JT ATI PROCHARGER: D1SC, D1, D1R	302ci. Max	3050 lbs.
WHIPPLECHARGER: 3.4 ATI PROCHARGER: F-1, F-1D, F-1A	302ci. Max	3150 lbs.
VORTECH: YS, YSI Trim, V24-YSI Trim ATI PROCHARGER: F-1C-91, F-1A-91	302ci. Max	3300 lbs.

* Manual transmission: Deduct 100 lbs.
 * Turbocharged cars with cast inducer wheel: deduct 100 lbs.
 * Cars with 289ci or smaller engines: Deduct 50 lbs.
 * Centrifugal Supercharged & Turbocharged cars with liquid intercooler: Add 100 lbs.