

If the rule is in **BLACK** text, then it is the same as 2025.

If the rule is in **BLUE** text, then it has been changed for 2026.

If any future revisions are made it will be in **RED** text.

Class Designation: RvS

General Safety: All vehicles must conform with general NHRA safety rules.

Turbo Crossbolts: Turbo crossbolts 3" from the turbine wheel is mandatory.

Engine Containment Device: Engine diaper with pigmat or catch pan device to capture oil and/or debris is mandatory. If a catch pan device is used, catch pan must have a minimum 2-inch-high lip on all sides. Lips must be covered or curved inward, so as to contain oil in pan. Catch pan must cover entire area below the engine. Catch pan must extend from radiator support to firewall and from frame rail to frame rail. In all cases, lips must be adequate enough to contain oil in the catch pan. Should a competitor spill excessive oil from the catch pan and debris onto the track, he or she may be disqualified from further competition at the sole and absolute discretion of the event director.

Beam Tripper: A front beam tripper is permitted but can only extend 45" forward of the centerline of the front wheel.

Engine Coolant: Only water is permitted in the coolant system. Antifreeze or other additives are prohibited.

Hybrids: Hybrids are permitted in this class (Import engines are permitted in Domestic bodies. Domestic engines are permitted in Import bodies.)

Body: Must have an import body or a domestic sport compact body.

Chassis: Any type chassis is permitted.

Fuel: Any fuel is permitted.

Turbochargers: Turbochargers are measured at the inducer wheel where the leading edge of the inducer wheel meets the housing. Compressor cover must be unmodified, it must be run the way it comes from the manufacturer. No porting of the surge port allowed.

Nitrous Oxide: Nitrous Oxide is prohibited.

Engine	Wheelbase	Clutch	Maximum Turbocharger	Nitrous Oxide	Tires	Car & Driver Minimum Weight
Rotary	96" Max	Adjustable Clutch ok	No Restrictions	Nitrous Prohibited	32"x14.5" max slick (radials prohibited)	1900 lbs.
4-cylinder	96" Max	Adjustable Clutch Prohibited Lock-Up or Flow Control Valve Prohibited	No Restrictions	Nitrous Prohibited	32"x14.5" max slick (radials prohibited)	1900 lbs.
6-cylinder	96" Max	Adjustable Clutch Prohibited Lock-Up or Flow Control Valve Prohibited	Any 91.9 mm single	Nitrous Prohibited	32"x14.5" max slick (radials prohibited)	2200 lbs.

Engine	Wheelbase	Clutch	Maximum Turbocharger	Nitrous Oxide	Tires	Car & Driver Minimum Weight
Any Engine	106" Max	Adjustable Clutch ok	No Restrictions	Nitrous Prohibited	28"x10.5" max slick (radials prohibited)	1900 lbs.